

Legacy Shade Installation Instructions



PRE-INSTALLATION

1. The top valance side, if applicable, are at least 2.5" deep.
2. The width of the shade is greater than the window and less than the window valance / side board.
3. You have the correct number of mounting clips and screws to complete the installation.

Finished shade assembly size:

29" or smaller = 3 clips

30" to 60" = 5 clips

61" to 80" = 6 clips

INSTALLATION

NOTE: For best results, all mounting clips should be securely mounted to the valance box and in a straight line. When mounting to an uneven or padded surface, it may be necessary to use solid spacers.

If possible, removal of the valance is preferred.

1. Remove the valance and turn upside down to remove old Day/Night Shade. Remove shade and mount clips in as described above. The outside clips should be mounted within 2" of adjusters to properly support shade.
2. center the shade assembly, snap the shade into the mounting clips. A flat blade screw driver may help pushing the rail into the clip.

Check shade operation:

For Combo Rollers

Turn the valance over and operate each shade looking at the back of the valance box. If additional tension is needed or the stop (height) needs adjusting see steps below.

Day shade (Lower Roller), turn the adjustment knob on the RIGHT SIDE CLOCKWISE one turn. Recheck tension, if more tension is needed add additional turns to desired tension. To adjust the height the roller stops, turn the adjustment knob on the LEFT side until the grab bar stops at the appropriate height.

Night Shade (Upper Roller) turn the adjustment knob on the LEFT SIDE COUNTER CLOCKWISE one turn. Recheck tension, if more tension is needed add additional turns to desired tension. To adjust the height the roller stops turn the adjustment knob on the RIGHT side until the grab bar stops at the appropriate height.

Be sure there are no obstructions that the grab bar would touch.

If you prefer to remove only your old shades, leaving the valance in place, mount the clips as instructed above. Snap the lead bar into the clips and adjust the height and tension as outlined above. Note: the tension and the height adjusters will be on the other side.



For Single Rollers

Turn the valance over and operate each shade looking at the back of the valance box. If additional tension is needed or the stop (height) needs adjusting see steps below.

Turn the adjustment knob on the LEFT SIDE COUNTER CLOCKWISE one turn. Recheck tension, if more tension is needed add additional turns to desired tension. To adjust the height the roller stops turn the adjustment knob on the LEFT side until the grab bar stops at the appropriate height.

Be sure there are no obstructions that the grab bar would touch.

If you prefer to remove only your old shades, leaving the valance in place, mount the clips as instructed above. Snap the lead bar into the clips and adjust the height and tension as outlined above. Note: the tension and the height adjusters will be on the other side.

